


| |
|----------|
| Date |
| Customer |
| Project |
| Type |


M-LED Module 70 1x LED 3000K Spot DE Black Matt



Specifications

| | |
|---------------------------------|----------------------------------|
| Material | 14070302 |
| Light Source Type | LED |
| LED Type | BRIDGELUX V8G8 |
| LED technology | LED COB |
| CRI | Min. 90 |
| Colour Temperature | 3000K |
| Lifetime | L90B10 @50,000 Hours |
| Lamp Included | Yes |
| Number of Light Sources | 1 |
| CIE flux code | 94 99 100 100 92 |
| Binning (SDCM) | 2 |
| Optic | Reflector |
| Input Voltage | Constant Current Driver Required |
| Electrical Class | III |
| IP Rating | 20 |
| Glow wire rating (°C) | 960 |
| Indoor/Outdoor | Indoor |
| Adjustability | Not Applicable |
| Distance to Lighted Object (m) | 0,1 |
| Primary Colour & Primary Finish | Black, Matt |
| Gross weight (g) | 183.0 |
| Drive current (mA) | 350 500 |
| Min. forward voltage (Vf) | 13,2 13,7 |
| Max. forward voltage (Vf) | 15,0 15,4 |
| Connected load (W) | 5,0 7,2 |
| Luminous flux per lamp (lm) | 532 713 |
| Efficacy (lm/W) | 106 99 |
| Glare rating | 21 22 |

TM30 & CRI diagram



Light distribution & beam diagram

