


Date
Customer
Project
Type

FFD_Vaeder Surface 1x LED 3000K 1-10V DI Black Structure - White Matt



With a name derived from the English verb ‘to evade’, it is clear from the start that Vaeder will be miles ahead of anything average. This fixture feels equally at home in an energy-efficient, ergonomic office environment and in a home office. Its characteristic honeycomb structure in combination with a wafer-thin diffuser minimises glare, while Vaeder’s ground-breaking LED technology results in an energy-efficient and high-performance office fixture.



Specifications

Material	14082172
Light Source Type	LED
LED Type	NLP
LED technology	LED PCB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	63 87 97 100 61
Binning (SDCM)	2
Light Direction	Down
Optic	Optic foil
Input Voltage	230V
Luminaire power (W)	36.0
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	1-10V
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Surface
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Secondary Colour & Secondary Finish	White, Matt
Gross weight (g)	5642.0
Luminous flux per lamp (lm)	2245
Efficacy (lm/W)	62
Glare rating	16

TM30 & CRI diagram



Light distribution & beam diagram

