


Date
Customer
Project
Type

FFD_Qbini Square Tapered 1x IP55 LED 3000K Medium DE Gold Matt



Specifications


Material	14152246	
Light Source Type	LED	
LED Type	CREE 1304	
LED technology	LED COB	
CRI	Min. 90	
Colour Temperature	3000K	
Lifetime	L90B10 @50,000 Hours	
Lamp Included	Yes	
Number of Light Sources	1	
Binning (SDCM)	2	
Light Direction	Down	
Optic	Reflector	
Measured beam angle (°)	24.7	
Input Voltage	Constant Current Driver Required	
Electrical Class	III	
IP Rating	55	
Glow wire rating (°C)	960	
Indoor/Outdoor	Indoor	
Application	Ceiling, Wall	
Adjustability	Not Applicable	
Distance to Lighted Object (m)	0,1	
Primary Colour & Primary Finish	Gold, Matt	
Gross weight (g)	221.0	
Drive current (mA)	350	500
Min. forward voltage (Vf)	7,5	7,8
Max. forward voltage (Vf)	9,5	9,8
Connected load (W)	3,0	4,4
Luminous flux per lamp (lm)	278	370
Efficacy (lm/W)	93	86
Glare rating	13	14
Remark	• Qbini Frame and Qbini Box not included • This is not a complete product. Qbini Frame or Qbini Box system required. • This is not a complete product. Qbini Frame or Qbini Box system required.	




MODULAR
LIGHTING —
INSTRUMENTS

FFD_Qbini Square Tapered 1x IP55 LED 3000K Medium DE
Gold Matt

TM30 & CRI diagram



Light distribution & beam diagram



Diagrams