


Date	
Customer	
Project	
Type	

Marbul Suspended Adjustable 109 1x LED 3000K Trailing Edge DI Black Structure




Specifications


Material	14233332
Light Source Type	LED
LED Type	CREE 1507
LED technology	LED COB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 88
Binning (SDCM)	2
Light Direction	Down
Optic	Reflector
Input Voltage	230V
Luminaire power (W)	11.0
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Suspended
Adjustability	H 360° V 45°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	1515.0
Delivered lumens (lm)	718
Efficacy (lm/W)	84
Glare rating	14
Remark	<ul style="list-style-type: none"> • Magnetic reflector not included • Longer suspension cable on request (standard length is 2 meter) • This is not a complete product. Magnetic reflector required. • This is not a complete product. Magnetic reflector required.

Marbul is a timeless, spherical accent luminaire. Its pure geometrical shape makes it easily fit in every interior. Why designers love it so? The attention to detail and the simplicity of the shape present a minimalistic, elegant and versatile design for those looking to experiment with organic lighting.

TM30 & CRI diagram



Light distribution & beam diagram



Diagrams

Optical Accessories

- 10216830

Reflector 82 Super Spot Aluminium Anodised
- 10216930

Reflector 82 Super Spot Champagne Anodised
- 10217030

Reflector 82 Super Spot Gold Anodised
- 10217130

Reflector 82 Medium Aluminium Anodised
- 10217230

Reflector 82 Medium Champagne Anodised
- 10217330

Reflector 82 Medium Gold Anodised
- 10217430

Reflector 82 Flood Aluminium Anodised
- 10217530

Reflector 82 Flood Champagne Anodised
- 10217630

Reflector 82 Flood Gold Anodised
- Choose a required accessory

Accessories