


Date
Customer
Project
Type

Marbul Suspended Adjustable 109 1x LED 3000K 1-10V/Push-Dim DI White Structure



Specifications

Material	14234309
Light Source Type	LED
LED Type	CREE 1507
LED technology	LED COB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 88
Binning (SDCM)	2
Light Direction	Down
Optic	Reflector
Input Voltage	230V
Luminaire power (W)	11.0
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	1-10V, Push-Dim
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Suspended
Adjustability	H 360° V 45°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	1515.0
Luminous flux per lamp (lm)	718
Efficacy (lm/W)	84
Glare rating	14

Marbul is a timeless, spherical accent luminaire. Its pure geometrical shape makes it easily fit in every interior. Why designers love it so? The attention to detail and the simplicity of the shape present a minimalistic, elegant and versatile design for those looking to experiment with organic lighting.

Remark	<ul style="list-style-type: none">• This is not a complete product. Discover the required accessories below.• Magnetic reflector not included• Longer suspension cable on request (standard length is 2 meter)• This is not a complete product. Magnetic reflector required.• This is not a complete product. Magnetic reflector required.
--------	--

TM30 & CRI diagram



Light distribution & beam diagram



Diagrams

Optical Accessories

- **10216830** Reflector 82 Super Spot Aluminium Anodised
- **10216930** Reflector 82 Super Spot Champagne Anodised
- **10217030** Reflector 82 Super Spot Gold Anodised
- **10217130** Reflector 82 Medium Aluminium Anodised
- **10217230** Reflector 82 Medium Champagne Anodised
- **10217330** Reflector 82 Medium Gold Anodised
- **10217430** Reflector 82 Flood Aluminium Anodised
- **10217530** Reflector 82 Flood Champagne Anodised
- **10217630** Reflector 82 Flood Gold Anodised

- Choose a required accessory