


Date
Customer
Project
Туре

Rektor Surface Adjustable 78x78 2x LED 2700K Flood Trailing Edge DI White Structure - White Structure



With a name derived from the Latin word for "ruler", the Rektor family has all the qualities of a leader. Strong, guiding, and arguably a good listener. Winner of the 2014 Henry Van de Velde design award, Rektor is an orientable downlighter that showcases the distinguished effects of right angles and accented light direction.





α			c·	, .		
7	ne	C11	tic	atı	ons	ı
~	ρ \circ	ر، ب	"		0.15	

Material	14246109			
Light Source Type	LED			
LED Type	BRIDGELUX VERO13			
LED technology	LED COB			
CRI	Min. 90			
Colour Temperature	2700K			
Lifetime	L80B20 @50,000 Hours			
Lamp Included	Yes			
Number of Light Sources	2			
Binning (SDCM)	3			
Light Direction	Down			
Optic	Reflector			
Measured beam angle (°)	38.6			
Input Voltage	230V			
Luminaire power (W)	25.7			
Electrical Class	1			
IP Rating	20			
Glow wire rating (°C)	960			
Dimming Protocol	Trailing Edge			
Indoor/Outdoor	Indoor			
Application	Ceiling, Wall			
Mounting	Surface			
Adjustability	H 360° V -90°/+90°			
Distance to Lighted Object (m)	0,1			
Primary Colour & Primary Finish	White, Structure			
Secondary Colour & Secondary Finish	White, Structure			
Gross weight (g)	2261.0			
Luminous flux per lamp (lm)	900			
Efficacy (Im/W)	70			
Glare rating	21			



TM30 & CRI diagram





Light distribution & beam diagram

