


Date
Customer
Project
Туре

## Rektor Track 230V Adjustable 78x78 1x LED 1800-3000K WD Medium Casambi DI White Structure



With a name derived from the Latin word for "ruler", the Rektor family has all the qualities of a leader. Strong, guiding, and arguably a good listener. Winner of the 2014 Henry Van de Velde design award, Rektor is an orientable downlighter that showcases the distinguished effects of right angles and accented light direction.





## Specifications

Material	14271009
Light Source Type	LED
LED Type	BRIDGELUX WARMDIM 12W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	97 100 100 100 85
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	26.0
Input Voltage	230V
Luminaire power (W)	14.5
Electrical Class	1
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Casambi
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	H 360° V -90°/+90°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Smart Lighting	Casambi
Gross weight (g)	817.0
Luminous flux per lamp (lm)	881
Efficacy (Im/W)	60
Glare rating	20
Remark	This is not a complete product. Track 230V system required.



## TM30 & CRI diagram





## Light distribution & beam diagram

