


Date
Customer
Project
Туре

Rektor Track 230V Adjustable 78x78 1x LED 1800-3000K WD Medium Casambi DI Black Structure



With a name derived from the Latin word for "ruler", the Rektor family has all the qualities of a leader. Strong, guiding, and arguably a good listener. Winner of the 2014 Henry Van de Velde design award, Rektor is an orientable downlighter that showcases the distinguished effects of right angles and accented light direction.





Specifications

Efficacy (Im/W)	56
Luminous flux per lamp (Im)	817
Gross weight (g)	817.0
Smart Lighting	Casambi
Primary Colour & Primary Finish	Black, Structure
Distance to Lighted Object (m)	0,1
Adjustability	H 360° V -90°/+90°
Application	Ceiling, Wall
Indoor/Outdoor	Indoor
Dimming Protocol	Casambi
Glow wire rating (°C)	960
IP Rating	20
Electrical Class	Ī
Luminaire power (W)	14.5
(°) Input Voltage	230V
Measured beam angle	26.0
Optic	Reflector
Light Direction	Down
Binning (SDCM)	3
Sources CIE flux code	97 100 100 100 85
Number of Light	1
Lamp Included	Yes
Lifetime	L80B10 @50,000 Hours
Colour Temperature	1800-3000K (Warm Dim)
CRI	Min. 95
LED technology	LED COB
LED Type	BRIDGELUX WARMDIM 12W
Light Source Type	LED
Material	14271032



TM30 & CRI diagram





Light distribution & beam diagram

