


Date
Customer
Project
Туре

Extruded Track 48V Suspended 46 300 1x LED 2700K Flood 1-10V Black Anodised - Silver Bronze Brushed
Anodised



This statement luminaire loves to play with light when it's on and when it's off. Its strong lines bring vertical structure to your space. The grooves along the shaft tell a different tale, every time the surrounding light changes. A cone-shape lampshade offers glare-free, intimate, accent light. Extruded is made for exchange. People to people, light to shadow.






١	p	e	c	ij	fications	
	_		-			

Material	13690025		
Light Source Type	LED		
LED Type	BRIDGELUX V6 HD G8		
LED technology	LED COB		
CRI	Min. 90		
Colour Temperature	2700K		
Lifetime	L80B10 @50,000 Hours		
Lamp Included	Yes		
Number of Light Sources	1		
CIE flux code	99 100 100 100 74		
Binning (SDCM)	2		
Light Direction	Down		
Optic	Reflector		
Measured beam angle (°)	42.0		
Input Voltage	48Vdc		
Luminaire power (W)	8.5		
Electrical Class	III		
IP Rating	20		
Glow wire rating (°C)	960		
Dimming Protocol	1-10V		
Indoor/Outdoor	Indoor		
Application	Ceiling		
Mounting	Suspended		
Distance to Lighted Object (m)	0,1		
Primary Colour & Primary Finish	Black, Anodised		
Secondary Colour & Secondary Finish	Silver Bronze, Brushed Anodised		
Gross weight (g)	1280.0		
Luminous flux per lamp (lm)	710		
Efficacy (Im/W)	84		
Glare rating	23		
Remark	This is not a complete product. Pista track 48V		

- system required.
- For installations without dimmer, it is





recommended to use 1-10 V luminaires.



TM30 & CRI diagram





Light distribution & beam diagram

