


Date
Customer
Project
Туре

Extruded Track 48V Suspended 46 600 1x LED 2700K Flood 1-10V Champagne Anodised - Champagne Brushed

Anodised



This statement luminaire loves to play with light when it's on and when it's off. Its strong lines bring vertical structure to your space. The grooves along the shaft tell a different tale, every time the surrounding light changes. A cone-shape lampshade offers glare-free, intimate, accent light. Extruded is made for exchange. People to people, light to shadow.



Specifications



	Specifications	
	Material	13690634
	Light Source Type	LED
	LED Type	BRIDGELUX V6 HD G8
	LED technology	LED COB
	CRI	Min. 90
	Colour Temperature	2700K
	Lifetime	L80B10 @50,000 Hours
	Lamp Included	Yes
	Number of Light Sources	1
	CIE flux code	98 100 100 100 76
	Binning (SDCM)	2
	Light Direction	Down
	Optic	Reflector
	Measured beam angle (°)	41.9
	Input Voltage	48Vdc
	Luminaire power (W)	8.5
	Electrical Class	III
	IP Rating	20
	Glow wire rating (°C)	960
	Dimming Protocol	1-10V
	Indoor/Outdoor	Indoor
	Application	Ceiling
	Mounting	Suspended
	Distance to Lighted Object (m)	0,1
	Primary Colour & Primary Finish	Champagne, Anodised
	Secondary Colour & Secondary Finish	Champagne, Brushed Anodised
	Gross weight (g)	1910.0
	Luminous flux per lamp (lm)	731
	Efficacy (Im/W)	86
	Glare rating	23

system required.

• This is not a complete product. Pista track 48V

Remark




Extruded Track 48V Suspended 46 600 1x LED 2700K Flood 1-10V Champagne Anodised - Champagne Brushed Anodised

recommended to use 1-10 V luminaires.



TM30 & CRI diagram





Light distribution & beam diagram

