


Date
Customer
Project
Туре

Extruded Track 48V Suspended 46 300 1x LED 3000K Flood DALI Black Anodised - Black Brushed Anodised



This statement luminaire loves to play with light when it's on and when it's off. Its strong lines bring vertical structure to your space. The grooves along the shaft tell a different tale, every time the surrounding light changes. A cone-shape lampshade offers glare-free, intimate, accent light. Extruded is made for exchange. People to people, light to shadow.





13690420

α		c.	, .	
7	ресі	<i>†1.C.C</i>	1110 i	ns
\smile		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	12

Material

Light Source Type	LED			
LED Type	BRIDGELUX V6 HD G8			
LED technology	LED COB			
CRI	Min. 90			
Colour Temperature	3000K			
Lifetime	L80B10 @50,000 Hours			
Lamp Included	Yes			
Number of Light Sources	1			
CIE flux code	99 100 100 100 74			
Binning (SDCM)	2			
Light Direction	Down			
Optic	Reflector			
Measured beam angle (°)	41.9			
Input Voltage	48Vdc			
Luminaire power (W)	8.5			
Electrical Class	III			
IP Rating	20			
Glow wire rating (°C)	960			
Dimming Protocol	DALI			
DALI Standard	DALI-2			
Indoor/Outdoor	Indoor			
Application	Ceiling			
Mounting	Suspended			
Distance to Lighted Object (m)	0,1			
Primary Colour & Primary Finish	Black, Anodised			
Secondary Colour & Secondary Finish	Black, Brushed Anodised			
Gross weight (g)	1280.0			
Luminous flux per lamp (lm)	731			
Efficacy (Im/W)	86			
Glare rating	24			
Remark	This is not a complete product. Pista track 48V			

- system required.
- For installations without dimmer, it is recommended to use 1-10 V luminaires.





TM30 & CRI diagram





Light distribution & beam diagram

