


|          |
|----------|
| Date     |
| Customer |
| Project  |
| Type     |

*Extruded Track 48V Suspended 46 300 lx LED 3000K Flood DALI Black Anodised - Champagne Brushed Anodised*



This statement luminaire loves to play with light when it's on and when it's off. Its strong lines bring vertical structure to your space. The grooves along the shaft tell a different tale, every time the surrounding light changes. A cone-shape lampshade offers glare-free, intimate, accent light. Extruded is made for exchange. People to people, light to shadow.



### Specifications

|                                     |                             |
|-------------------------------------|-----------------------------|
| Material                            | 13690423                    |
| Light Source Type                   | LED                         |
| LED Type                            | BRIDGELUX V6 HD G8          |
| LED technology                      | LED COB                     |
| CRI                                 | Min. 90                     |
| Colour Temperature                  | 3000K                       |
| Lifetime                            | L80B10 @50,000 Hours        |
| Lamp Included                       | Yes                         |
| Number of Light Sources             | 1                           |
| CIE flux code                       | 98 100 100 100 76           |
| Binning (SDCM)                      | 2                           |
| Light Direction                     | Down                        |
| Optic                               | Reflector                   |
| Measured beam angle (°)             | 41.9                        |
| Input Voltage                       | 48Vdc                       |
| Luminaire power (W)                 | 8.5                         |
| Electrical Class                    | III                         |
| IP Rating                           | 20                          |
| Glow wire rating (°C)               | 960                         |
| Dimming Protocol                    | DALI                        |
| DALI Standard                       | DALI-2                      |
| Indoor/Outdoor                      | Indoor                      |
| Application                         | Ceiling                     |
| Mounting                            | Suspended                   |
| Distance to Lighted Object (m)      | 0,1                         |
| Primary Colour & Primary Finish     | Black, Anodised             |
| Secondary Colour & Secondary Finish | Champagne, Brushed Anodised |
| Gross weight (g)                    | 1280.0                      |
| Luminous flux per lamp (lm)         | 746                         |
| Efficacy (lm/W)                     | 88                          |
| Glare rating                        | 24                          |

---

Remark

- This is not a complete product. Pista track 48V system required.
  - For installations without dimmer, it is recommended to use 1-10 V luminaires.
-

**TM30 & CRI diagram**



**Light distribution & beam diagram**

