


Date	
Customer	
Project	
Туре	

Extruded Track 48V Suspended 46 300 1x LED 3000K Flood DALI Black Anodised - Champagne Brushed Anodised



This statement luminaire loves to play with light when it's on and when it's off. Its strong lines bring vertical structure to your space. The grooves along the shaft tell a different tale, every time the surrounding light changes. A cone-shape lampshade offers glare-free, intimate, accent light. Extruded is made for exchange. People to people, light to shadow.





Specifications	
Material	13690423
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G8
LED technology	LED COB
CBI	Min 90

OB Min. 90 Colour Temperature 3000K L80B10 @50,000 Hours Lifetime Lamp Included Yes Number of Light 1 Sources CIE flux code 98 100 100 100 76 Binning (SDCM) 2 Light Direction Down Optic Reflector Measured beam angle 41.9 Input Voltage 48Vdc Luminaire power (W) 8.5 **Electrical Class** Ш IP Rating 20 Glow wire rating (°C) 960 Dimming Protocol DALI **DALI Standard** DALI-2 Indoor/Outdoor Indoor Application Ceiling Mounting Suspended Distance to Lighted 0,1 Object (m) Primary Colour & Black, Anodised Primary Finish Secondary Colour & Champagne, Brushed Anodised Secondary Finish 1280.0 Gross weight (g) Luminous flux per lamp 746 Efficacy (Im/W) 88 Glare rating 24 Remark • This is not a complete product. Pista track 48V system required.


> For installations without dimmer, it is recommended to use 1-10 V luminaires.





TM30 & CRI diagram





Light distribution & beam diagram

