


Date	
Customer	
Project	
Туре	

Extruded Track 48V Suspended 46 600 1x LED 1800-3000K WD Flood 1-10V Grey White Structure - Grey White Matt



This statement luminaire loves to play with light when it's on and when it's off. Its strong lines bring vertical structure to your space. The grooves along the shaft tell a different tale, every time the surrounding light changes. A cone-shape lampshade offers glare-free, intimate, accent light. Extruded is made for exchange. People to people, light to shadow.





α ·	c·	
naci	ticati	ONG
Specij	ıcaıı	OUO
r - r - r - r - r - r - r - r - r - r -		

Material	13690836
Light Source Type	LED
LED Type	BRIDGELUX WARMDIM 6W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	97 100 100 100 83
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	47.3
Input Voltage	48Vdc
Luminaire power (W)	6.0
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	1-10V
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Suspended
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Grey White, Structure
Secondary Colour & Secondary Finish	Grey White, Matt
Gross weight (g)	1910.0
Luminous flux per lamp (lm)	418
Efficacy (Im/W)	70
Glare rating	22
Remark	This is not a complete product. Pista track 48V overton required.

system required.For installations without dimmer, it is



Extruded Track 48V Suspended 46 600 1x LED 1800-3000K WD Flood 1-10V Grey White Structure - Grey White Matt

recommended to use 1-10 V luminaires.



TM30 & CRI diagram





Light distribution & beam diagram

