


|          |
|----------|
| Date     |
| Customer |
| Project  |
| Type     |

*Extruded Track 48V Suspended 46 900 1x LED 3000K Flood 1-10V Black Anodised - Champagne Brushed Anodised*



This statement luminaire loves to play with light when it's on and when it's off. Its strong lines bring vertical structure to your space. The grooves along the shaft tell a different tale, every time the surrounding light changes. A cone-shape lampshade offers glare-free, intimate, accent light. Extruded is made for exchange. People to people, light to shadow.



### Specifications

|                                     |   |
|-------------------------------------|---|
| Material                            | 13691323  |
| Light Source Type                   | LED   |
| LED Type                            | BRIDGELUX V6 HD G8  |
| LED technology                      | LED COB   |
| CRI                                 | Min. 90   |
| Colour Temperature                  | 3000K   |
| Lifetime                            | L80B10 @50,000 Hours  |
| Lamp Included                       | Yes   |
| Number of Light Sources             | 1   |
| CIE flux code                       | 98 100 100 100 76   |
| Binning (SDCM)                      | 2   |
| Light Direction                     | Down  |
| Optic                               | Reflector   |
| Measured beam angle (°)             | 41.9  |
| Input Voltage                       | 48Vdc   |
| Luminaire power (W)                 | 8.5   |
| Electrical Class                    | III   |
| IP Rating                           | 20  |
| Glow wire rating (°C)               | 960   |
| Dimming Protocol                    | 1-10V   |
| Indoor/Outdoor                      | Indoor  |
| Application                         | Ceiling   |
| Mounting                            | Suspended   |
| Distance to Lighted Object (m)      | 0,1   |
| Primary Colour & Primary Finish     | Black, Anodised   |
| Secondary Colour & Secondary Finish | Champagne, Brushed Anodised   |
| Gross weight (g)                    | 2485.0  |
| Luminous flux per lamp (lm)         | 746   |
| Efficacy (lm/W)                     | 88  |
| Glare rating                        | 24  |
| Remark                              | <ul style="list-style-type: none"> <li>• This is not a complete product. Pista track 48V system required.</li> <li>• For installations without dimmer, it is recommended to use 1-10 V luminaires.</li> </ul> |



**TM30 & CRI diagram**



**Light distribution & beam diagram**

