


Date
Customer
Project
Type

*Extruded Track 48V Suspended 46 900 lx LED 1800-3000K WD Flood 1-10V Black Anodised - Silver Bronze  
 Brushed Anodised*



This statement luminaire loves to play with light when it's on and when it's off. Its strong lines bring vertical structure to your space. The grooves along the shaft tell a different tale, every time the surrounding light changes. A cone-shape lampshade offers glare-free, intimate, accent light. Extruded is made for exchange. People to people, light to shadow.



### Specifications

Material	13691425
Light Source Type	LED
LED Type	BRIDGELUX WARMDIM 6W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	98 100 100 100 78
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	45.9
Input Voltage	48Vdc
Luminaire power (W)	6.0
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	1-10V
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Suspended
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Anodised
Secondary Colour & Secondary Finish	Silver Bronze, Brushed Anodised
Gross weight (g)	2485.0
Luminous flux per lamp (lm)	394
Efficacy (lm/W)	66
Glare rating	22
Remark	<ul style="list-style-type: none"> <li>• This is not a complete product. Pista track 48V system required.</li> <li>• For installations without dimmer, it is</li> </ul>



**MODULAR**  
LIGHTING —  
INSTRUMENTS

*Extruded Track 48V Suspended 46 900 lx LED 1800-3000K WD  
Flood 1-10V Black Anodised - Silver Bronze Brushed Anodised*

recommended to use 1-10 V luminaires.

TM30 &amp; CRI diagram



Light distribution &amp; beam diagram

