




Date
Customer
Project
Type

Extruded Track 48V Suspended 46 900 Ix LED 2700K Flood DALI Black Anodised - Champagne Brushed Anodised




### Specifications

Material	13691523
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	98 100 100 100 76
Binning (SDCM)	2
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	41.9
Input Voltage	48Vdc
Luminaire power (W)	8.5
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI
DALI Standard	DALI-2
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Suspended
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Anodised
Secondary Colour & Secondary Finish	Champagne, Brushed Anodised
Gross weight (g)	2485.0
Luminous flux per lamp (lm)	731
Efficacy (lm/W)	86
Glare rating	23
Remark	<ul style="list-style-type: none"><li>This is not a complete product. Pista track 48V system required.</li><li>For installations without dimmer, it is recommended to use 1-10 V luminaires.</li></ul>

This statement luminaire loves to play with light when it's on and when it's off. Its strong lines bring vertical structure to your space. The grooves along the shaft tell a different tale, every time the surrounding light changes. A cone-shape lampshade offers glare-free, intimate, accent light. Extruded is made for exchange. People to people, light to shadow.



**TM30 & CRI diagram**

**Light distribution & beam diagram**
